
Arizona



Scope of Application

Application appropriate for medium-heavy use in many branches of industry, disposal and agriculture. Is applicable inter alia as agricultural manure hose, communal vehicles or irrigation systems. • Smooth on the inside

Construction

 Comes with a shock-resistant, hard PVC spiral, overlaying to the outside as green abrasion protection

Properties

• PVC suction / pressure hose that is flexible at low temperature

Temperature range

-25°C to +60°

Article no.	Ø	Wall thikness	kg	R		_ <u>#</u>	
	25 mm	4,4 mm	0,5 kg/m	100 mm	101 psi	304 psi	50 m
	32 mm	4,4 mm	0,6 kg/m	130 mm	87 psi	261 psi	50 m
	38 mm	4,4 mm	0,7 kg/m	150 mm	87 psi	261 psi	50 m
	45 mm	5,0 mm	0,9 kg/m	180 mm	79 psi	239 psi	20 m
280380	50 mm	5,5 mm	1,05 kg/m	200 mm	72 psi	217 psi	50 m
	60 mm	5,6 mm	1,25 kg/m	240 mm	65 psi	195 psi	50 m
	63 mm	6,0 mm	1,39 kg/m	250 mm	65 psi	195 psi	50 m
	75 mm	6,5 mm	1,7 kg/m	300 mm	58 psi	174 psi	50 m
280383	76 mm	6,5 mm	1,7 kg/m	300 mm	58 psi	174 psi	50 m
280390	80 mm	6,5 mm	1,85 kg/m	320 mm	50 psi	152 psi	50 m
	89 mm	6,7 mm	2,25 kg/m	360 mm	50 psi	152 psi	50 m
280385	90 mm	6,7 mm	2,25 kg/m	360 mm	50 psi	152 psi	50 m
	100 mm	7,4 mm	2,7 kg/m	400 mm	43 psi	130 psi	50 m
280386	102 mm	7,3 mm	2,7 kg/m	400 mm	43 psi	130 psi	50 m
280387	110 mm	7,5 mm	3,1 kg/m	440 mm	43 psi	130 psi	20 m
	120 mm	8,0 mm	3,6 kg/m	480 mm	36 psi	108 psi	20 m
	125 mm	8,3 mm	3,9 kg/m	500 mm	36 psi	108 psi	20 m
280388	127 mm	8,3 mm	3,9 kg/m	510 mm	36 psi	108 psi	20 m
	130 mm	8,5 mm	4,1 kg/m	520 mm	36 psi	108 psi	20 m
	133 mm	8,5 mm	4,2 kg/m	550 mm	29 psi	101 psi	20 m
	150 mm	9,0 mm	5,0 kg/m	600 mm	29 psi	87 psi	20 m
280389	152 mm	9,0 mm	5,0 kg/m	610 mm	29 psi	87 psi	20 m
	160 mm	9,4 mm	5,6 kg/m	640 mm	29 psi	87 psi	20 m
281621	200 mm	13,0 mm	10,0 kg/m	800 mm	21 psi	65 psi	-