

# foxiGarant PUR H



## Scope of Application

Universally usable suction and blower hose, particularly in the area of coarse-grained / sharp-edged media with high flow-rate (blasting materials , chips , paper). Applicable for usage as standard hose for industrial vacuum cleaners, for granule conveyors (abrasive synthetic materials), for suction of paper fibers, for gaseous and liquid media or suction at vacuum pumps.

## Properties

- Heavy design (wall thickness approx. 1.45 mm)
- Highly flexible
- Smooth on the inside
- Highly abrasion-resistant
- Higher resistance to pressure and vacuum

- Antistatic
- Bacteria-resistant and hydrolysis-stabilized
- Flame-resistant according to DIN 4102 B1







## Construction

- Hoch abriebfestes Polyester Polyurethan
- Wandstärke: ca. 1,45 mm
- Spirale: Federstahldraht, verkuft

## Temperature Range

- -40°C to +90°C, for a short time up to +125°C

On request, additional nominal sizes available.

Article no.			Vacuum				
<b>284000</b>	80 mm	29,01 psi	8,53 psi	132 mm	91 mm	1,11 kg/m	10 m, 15 m, 20 m
<b>284001</b>	100 mm	21,76 psi	6,40 psi	165 mm	112 mm	1,48 kg/m	10 m, 15 m, 20 m
<b>284002</b>	125 mm	18,86 psi	4,44 psi	203 mm	138 mm	1,91 kg/m	10 m, 15 m, 20 m
<b>284003</b>	150 mm	15,23 psi	3,55 psi	242 mm	163 mm	2,29 kg/m	10 m, 15 m, 20 m
<b>284004</b>	200 mm	10,88 psi	2,67 psi	321 mm	215 mm	3,30 kg/m	10 m, 15 m, 20 m