




## Calibration Hoses




Calibration hoses can be utilized as an auxiliary means for installation purposes in route rehabilitation. These enable a rehabilitation with an open end if there is either a particular part of the pipe that needs to be redeveloped or there is no possibility to open the liner afterwards

### Beige (unstitched, up to 80°C, bendable up to 90°C)

Article no.	Nominal width	
282714-50	DN 100	50 m
282714-100	DN 100	100 m
282715-50	DN 125	50 m
282715-100	DN 125	100 m
282716-50	DN 150	50 m
282716-100	DN 150	100 m
282717-50	DN 200	50 m
282717-100	DN 200	100 m


### Orange (welded, up to 80°C, bendable up to 90°C)

Article no.	Nominal width	
282331-50	DN 100	50 m
282331-100	DN 100	100 m
282332-50	DN 125	50 m
282332-100	DN 125	100 m
282333-50	DN 150	50 m
282333-100	DN 150	100 m
282334-50	DN 200	50 m
282334-100	DN 200	100 m
282335-50	DN 250	50 m
282335-100	DN 250	100 m
282336-50	DN 300	50 m
282336-100	DN 300	100 m



# Frauenhof

Purple (welded, up to 50°C, extremely bendable)

Article no.	Nominal width	
282714-50	DN 100	50 m
282714-100	DN 100	100 m
282715-50	DN 125	50 m
282715-100	DN 125	100 m
282716-50	DN 150	50 m
282716-100	DN 150	100 m
282717-50	DN 200	50 m
282717-100	DN 200	100 m