





Sava Test Sealing Cushions







Test sealing cushions are characterized by their economical construction. Up to a size of 200 mm, they are equipped with a car tire inflation valve that is integrated into the plug. Plugs of other sizes are endowed with quick couplings. Eyelet rings on the plugs facilitate lifting and lowering.

Test Sealing Cushions

| Article no. | Scope of application Min \varnothing / Max. \varnothing |  |  kg |  |  | Bypass-Interior \varnothing |
|-------------|---|---|--|---|---|-------------------------------|
| 270150 | 100/200 | 2,5 bar | 2,60 kg | 350 mm | 68 mm | 1" |
| 270151 | 150/300 | 2,5 bar | 4,40 kg | 590 mm | 142 mm | 1" |
| 270152 | 200/400 | 2,5 bar | 6,30 kg | 635 mm | 192 mm | 2" |
| 270153 | 350/600 | 2,5 bar | 16,60 kg | 868 mm | 322 mm | 2" |
| 270161 | 500/800 | 2,5 bar | 31,30 kg | 1185 mm | 472 mm | 2" |
| 270120 | 500/1000 | 1,5 bar | 31,30 kg | 1185 mm | 472 mm | 2" |

Test Sealing Cushions Short

| Article no. | Scope of application Min \varnothing / Max. \varnothing |  |  kg |  |  | Bypass-Interior \varnothing |
|-------------|---|---|--|---|---|-------------------------------|
| 270154 | 46/52 | 2,5 bar | 0,17 kg | 110 mm | 45 mm | 1/8" |
| 270155 | 71/77 | 2,5 bar | 0,32 kg | 115 mm | 70 mm | 1/2" |
| 270156 | 86/102 | 2,5 bar | 0,59 kg | 175 mm | 85 mm | 1/2" |
| 270157 | 143/153 | 2,5 bar | 1,88 kg | 220 mm | 142 mm | 1" |
| 270158 | 71/102 | 2,5 bar | 0,35 kg | 130 mm | 70 mm | 1/2" |
| 270159 | 86/153 | 2,5 bar | 0,63 kg | 195 mm | 85 mm | 1/2" |
| 270160 | 143/204 | 2,5 bar | 2,03 kg | 250 mm | 142 mm | 1" |