







## 1 SN



This ultra high pressure hose is used for sewer and pipe cleaning purposes. The 1 SN hoses is suitable for hydraulic oils both mineral and biological, oils based on polyglycol, water-oil emulsions and water.

- Temperature range: -40°C to +100°C
- Inner tube: Synthetic rubber
- Pressure carrier: high-strength steel wire mesh
- Cover: Synthetic rubber, MSHA flame retardant approved

Nominal width						
<b>DN8</b>	12,7 mm	15,0 mm	3.100 psi	12.400 psi	115 mm	0,24 kg/m
<b>DN12</b>	18,3 mm	20,6 mm	2.320 psi	9.200 psi	180 mm	0,41 kg/m
<b>DN16</b>	21,4 mm	23,7 mm	1.880 psi	7.500 psi	200 mm	0,45 kg/m
<b>DN19</b>	25,4 mm	27,7 mm	1.500 psi	6.000 psi	240 mm	0,58 kg/m

### Article Numbers:

Length/Nominal width	20m	40m	50m	60m	80m	100m	120m
<b>DN8</b>	280854	280855	-	-	280856	-	-
<b>DN12</b>	280857	280858	280480	280108	280859	282732	280860
<b>DN16</b>	-	-	-	-	281580	-	280311
<b>DN19</b>	-	280861	-	-	280862	-	280450

All the hose lines listed in the table are fully and properly integrated with fittings.