








Trelleborg Canalkler 250S



This ultra high pressure hose is used in sewer and pipe cleaning. It is characterized by the texture of its extremely smooth upper cover in particular. As a result, both its abrasion value and its sliding behavior are highly valued performance characteristics of its users. They are definitely the benchmark defining what is currently feasible.

The 250 S is manufactured in accordance with the regulations of the trade association (ZH1 / 406).

- Temperature range: -35°C to 80°C
- Inner tube: SBR black, smooth
- Pressure carrier: 2 braided textile inserts
- Cover: NR/BR black, smooth

Nominal width						
DN13	13,0 mm	25,6 mm	3625 psi	9065 psi	70 mm	0,45 kg/m
DN19	19,0 mm	31,6 mm	3625 psi	9065 psi	90 mm	0,61 kg/m
DN25	25,0 mm	39,3 mm	3625 psi	9065 psi	100 mm	0,9 kg/m
DN32	32,0 mm	47,6 mm	3625 psi	9065 psi	130 mm	1,12 kg/m
DN38	38,0 mm	54,0 mm	3625 psi	9065 psi	155 mm	1,35 kg/m

Article Numbers:

Length/Nominal width	20m	40m	60m	80m	120m	150m	160m	180m	200m	240m
DN13	282623	282040	282042	282044	282046	-	-	-	-	-
DN19	-	282048	282612	282050	282052	-	-	-	-	-
DN25	-	282054	282613	282056	282058	-	282060	282062	282201	281978
DN32	-	282064	282614	282066	282068	-	282070	282072	282663	-
DN38	-	282074	-	282076	282078	282080	-	-	-	-

All the hose lines listed in the table are fully and properly integrated with fittings.