


Semperit IK 25









This ultra high pressure hose is used in sewer and pipe cleaning purposes. Due to its outstanding price-performance ratio, it is one of the most attractive hoses on the market. It is characterized by both its weather-resistant hose cover and its particularly corrosion-resistant fittings. These properties provide the product from the house of Semperit with a high wear protection.

The IK 25 is manufactured according to the regulations of the occupation cooperative (ZH1/406).

- Temperature range: -35°C to 80°C
- Inner tube: SBR black, smooth
- Pressure carrier: 2 braided textile inserts
- Cover: NR/BR black, smooth

This hose can also be manufactured as a front hose on all sizes.

Nominal width						
DN13	13,0 mm	25,0 mm	3625 psi	9065 psi	70 mm	0,46 kg/m
DN19	19,0 mm	31,0 mm	3625 psi	9065 psi	95 mm	0,61 kg/m
DN25	25,0 mm	39,0 mm	3625 psi	9065 psi	110 mm	0,86 kg/m
DN32	32,0 mm	48,0 mm	3625 psi	9065 psi	150 mm	1,27 kg/m

Article Numbers:

Length/ Nominal width	20m	40m	60m	80m	120m	160m	180m	200m	220m	240m
DN13	286028	286000	286001	286002	286003	-	-	-	-	-
DN19	-	286004	286027	286005	286006	-	-	-	-	-
DN25	-	286007	-	286008	286009	286010	286011	286030	286012	286031
DN32	-	286013	286013	286014	286015	286016	286017	-	-	-

All the hose lines listed in the table are fully and properly integrated with fittings.