








Transfer Oil Ecology 200



This ultra high pressure hose is used for sewer and pipe cleaning purposes. The Ecology 200 has a weight saving of 30% compared to other rubber sewer cleaning hoses. The thermoplastic polymer is characterized by excellent abrasion values and cut resistance and therefore has a long service life. The blue hose cover is also resistant to microbiological attacks.

- Temperature range: -40°C to +60°C
- Inner tube: Thermoplastic polymer
- Pressure carrier: 2 braidings of highly tear-resistant synthetic fibers and an additional braid
- Cover: Polyurethane, blue, extremely cut- and abrasion-resistant

Nominal width						
DN13	13,0 mm	21,4 mm	2.900 psi	7.250 psi	75 mm	0,23 kg/m
DN19	19,6 mm	29,7 mm	2.900 psi	7.250 psi	120 mm	0,41 kg/m
DN25	25,6 mm	37,5 mm	2.900 psi	7.250 psi	155 mm	0,61 kg/m
DN32	32,4 mm	47,2 mm	2.900 psi	7.250 psi	240 mm	1,00 kg/m
DN38	38,4 mm	55,6 mm	2.900 psi	7.250 psi	300 mm	1,34 kg/m

Article Numbers:

Length/ Nominal width	40m	60m	80m	120m	160m	180m	200m	240m
DN13	280433	280434	280435	280436	-	-	-	-
DN19	280437	280438	280439	280440	280441	-	-	-
DN25	-	-	-	280400	280401	280402	280432	280403
DN32	-	-	-	280801	280404	280405	280432	280430
DN38	-	-	-	-	-	-	-	-

All the hose lines listed in the table are fully and properly integrated with fittings.