



## Connectors

	Article no.	Description	 (Main element)	 (complete)	DN (Ø flow)	
	<b>283940</b>	For male M14 x 1,5 left and 2 thrust screws male M26 x 1,5	46mm	73mm	5	58.000 psi
	<b>282446</b>	For Male M20 x 1,5 LH with mounting for thrust ring on both sides thrust ring male M36 x 2	83mm	121mm	9	58.000 psi
	<b>283931</b>	Angled Block 90° Male M14 x 1,5 LH and 2 thrust screws male M26 x 1,5	50mm	64mm	5	58.000 psi
	<b>283932</b>	T-piece male M14 x 1,5 LH and 3 thrust screws male M26 x 1,5	50mm	77 x 64mm	5	58.000 psi
	<b>283938</b>	For 3/8 – 24 UNF LH with 2 thrust rings and screws	42mm	70mm	3	58.000 psi
	<b>282442</b>	For Male M14 x 1,5 LH large with holder for large thrust ring, both sides thrust screw male M30 x 2 (large model of 283940)	47mm	83mm	5	58.000 psi
	<b>160487</b>	Both sides female 9/16-18 UNF LH	60mm	60mm	5,5	36.250 psi
	<b>160488</b>	Both sides female 1/4" BSP	46mm	46mm	5	21.750 psi
	<b>160489</b>	Both sides female 1/4" BSP (IG)	46mm	46mm	5	15.950 psi
	<b>160490</b>	Both sides female 1/8" BSP (IG)	32mm	32mm	4,5	14.500 psi



# Frauenhof



<b>160491</b>	Both sides female M7 (IG)	30mm	30mm	3	17.400 psi
---------------	---------------------------	------	------	---	------------



<b>160492</b>	Both sides female M5 incl. POM-sealing	30mm	30mm	1,5	15.950 psi
---------------	--	------	------	-----	------------