


Polyflex PFX25



The new PFX25 ultra-high-pressure water jet hose has been specially designed for your high-pressure applications. It is used in various industries requiring pressures of up to 2,500 bar. The new six-wire design significantly reduces weight compared to the eight-wire version. Additionally, a highly abrasion-resistant Tough-Jacket version is available for more extreme conditions.

Compared to previous hoses, the PFX25 offers you the following advantages:

- suitable for applications up to 2500 bar
- improved service life
- high robustness
- low weight
- colour: grey

Technical Data:

- inner tube: POM
- pressure carrier: six spiral inserts made of steel wire with maximum tensile strength
- cover: polyamide (optionally with second top cover made of Tough Jacket material)
- temperature: -10°C to +70°C

Description						
4	4,0 mm	9,9 mm	36.250 psi	90.650 psi	120 mm	0,22 kg/m
5	4,9 mm	12,9 mm	36.250 psi	90.650 psi	175 mm	0,41 kg/m
6	6,4 mm	14,6 mm	36.250 psi	90.650 psi	200 mm	0,55 kg/m
8	7,8 mm	18,0 mm	36.250 psi	90.650 psi	200 mm	0,85 kg/m
8-TJ*	7,8 mm	22,0 mm	36.250 psi	90.650 psi	200 mm	1,00 kg/m

Suitable Fittings:

Fittings	PFX25-4	PFX25-5	PFX25-6	PFX25-8
Swivel nut DKOS M16 x 1,5	X			
Male 1/4"	X			
Male M14 x 1,5 LH	X		X	X
Male 1/4" – 28 UNF LH	X	X		
Male 1/4" – 28 UNF RE	X			
Male 1/4" – 28 UNF kurz	X			
Male 3/8 – 24 UNF LH	X	X	X	X
Male 9/16 – 18 UNF		X	X	X
Swivel nut 9/16"-18 UNF LH	X		X	
Swivel nut 3/4" – 16 UNF		X		X
LOK DN5/DN8		X		X