## **PowerJet**



- high flexibility
- robustness
- inner tube: synthetic rubber compound
- pressure carrier: 4 (WB2/WB15), 4+1 (WB20) or 6 (WB3) layers of high-strength steel wire
- cover: synthetic rubber compound (especially abrasion resistant and resistant against external influences)
- Temperature:

## WB 15/ WB 20:

Basically up to 100°C

- 70°C to 90 °C Safety factor raised to 3:1
- Über 90°C Safety factor raised to 4:1

## WB 2:

• -40°C to +80°C

Descrip- tion	DN	Article-no.	Ø	Ø		*	A	kg
WB2	10	282374-08	9,5-10,5 mm	20,8 mm	18.150 psi	45.325 psi	230 mm	0,85-0,9 kg/m
	12	282367	12,5-13,5 mm	24,6 mm	15.950 psi	39.875 psi	230 mm	1,24-1,26 kg/m
	20	282369	18,5-20,5 mm	32,0 mm	14.500 psi	36.250 psi	250 mm	1,78-1,87 kg/m
WB15	10	282374-08-H	9,5-10,5 mm	21,4 mm	18.150 psi	45.325 psi	230 mm	0,85-0,9 kg/m
	12	282367-H	12,5-13,5 mm	25,4 mm	15.950 psi	39.875 psi	230 mm	1,24-1,26 kg/m
	20	282369-H	18,5-20,5 mm	31,8 mm	14.500 psi	36.250 psi	250 mm	1,78-1,87 kg/m
WB3	10	282375	9,5-10,5 mm	22,2 mm	19.580 psi	50.760 psi	150 mm	1,10 kg/m
	12	280810	12,5-13,5 mm	29,0 mm	20.300 psi	52.575 psi	250 mm	1,75-1,87 kg/m
	20	282380	18,5-20,5 mm	34,0 mm	19.580 psi	48.950 psi	300 mm	2,14 kg/m
WB20	12	280810-H	12,5-13,5 mm	29,5 mm	20.300 psi	50.760 psi	200 mm	1,75-1,87 kg/m
	20	283370	19,0 mm	35,0 mm	20.300 psi	50.760 psi	300 mm	2,53 kg/m

## **Suitable Fittings:**

Fittings	DN10	DN12	DN20
Swivel nut M24 x 1,5	X	X	
Swivel nut M36 x 2			X